



Data sheet for Metric Hexagon Rivet Nuts Metric Hole Sizes

Thread Pitch	Grip Range mm Min / Max	D +/- 0.20	K +/- 0.15	Ød +0.00 -0.15	Hole Size A/F +0.10 -0.00	L +/- 0.30	Approximate Height after Installation
M3 x 0.5 *	0.50-1.50	5.50	0.35	4.90	5.00	8.50	5.50
M4 x 0.7	0.50-2.00	6.80	0.50	5.90	6.00	10.50	6.50
	2.00-3.00					11.50	
M5 x 0.8	0.50-3.00	8.00	0.60	6.90	7.00	11.50	7.50
	2.00-4.00					13.50	
M6 x 1.0	0.50-3.00	10.00	0.60	8.90	9.00	14.50	9.00
	3.00-6.00					17.50	
M8 x 1.25	0.50-3.00	12.00	0.60	10.90	11.00	16.50	11.00
	3.00-6.00					19.50	
M10 x 1.50	1.00-2.50	13.50	0.85	11.90	12.00	16.50	12.50
	2.50-4.00					18.50	

Finishes

Zinc / Yellow Chromate Passivation , Zinc Trivalent Chromate (RoHS compliant to order)

Material

Mild Steel
 Stainless Steel (A2)
 Aluminium *

* Please check for availability

